

Air Purifier

HITACHI



究極の理想



THE EPITOME OF DESIRE




Our Air Purifiers are Made in Japan. And Stocked with Innovative Features.

Harnessing the best of Hitachi technology, we derive immense pleasure in delivering powerful air purifiers through proprietary technologies. Its unique air purifying filtration system keeps the living space clean and comfort.

Hitachi Made in Japan air purifiers exude external aesthetic beauty and are also made for the intelligent and innovative homes of the future.
With Hitachi, you've got it made.

Auto Self Clean – Auto Filter Cleaning Robot

The pre-filter is automatically cleaned before dust accumulates for easier maintenance.



A brush moves up and down to remove dust.

Allergen-free HEPA & Washable Deodorising Filter

Ready to remove a variety of dirt and odours from the air, including fine dust and allergens.



Can be washed with water




EP-L110E

PM 2.5*1	Free-floating viruses*2	Free-floating bacteria*2	Cedar pollen*3
Ragweed pollen*3	Birch pollen*3	Dust mite excreta*3	Cat dander*3
Ammonia*2 (pet odours, etc.)	Trimethylamine*2 (rotten fish odours, etc.)	Acetaldehyde*2 (tobacco odours, etc.)	Isovaleraldehyde*2 (barbecued/broiled meat odours, etc.)
Acetic acid*2 (pickled vegetable odours, etc.)	Isovaleric acid*2 (body odour, room-dried clothes odour, etc.)	Hydrogen sulfide*4 (drain/toilet odours)	Methylmercaptan*4 (rotten vegetable odours)

Wide & Speedy Dust Collection

Speedy air purifying with massive volume of 11m³ per minute. Applicable to a 79m² floor space.



*1 Effect in a 32m³ enclosed space
*2 Effect in a 25m³ enclosed space
*3 Suppression effect on cedar, ragweed and birch pollen, dust mite excreta, cat dander and other substances containing allergens
*4 Test results in a 1m³ test chamber



Hitachi's Air Purifiers were awarded the Allergy UK Seal of Approval in recognition of their proven ability to reduce exposure to allergens.

- Tested by Allergy UK (The British Allergy Foundation)
- Tested with house dust mites and pollen



Easy Maintenance & Cleaning

Auto Self Clean – Auto Filter Cleaning Robot

When the Auto Self Clean unit operates, it moves up and down while brushing the pre-filter to remove dust, which is then collected in the dust box.

Auto Self Clean Unit

- At the time of shipment, the Auto Self Clean function is switched off
- The Auto Self Clean unit is mounted on the rear panel of the air purifier
- Operates once after every 48 hours (cumulative) of air purifier operation



Pre-filter comparison after 1 month of operation*2

With Auto Self Clean, the pre-filter is clean

Without Auto Self Clean

*2 Based on test results using the Auto Operation mode in an approx. 30m² living room.

Auto Self Clean Manual (press for 3 sec)

You can also start automatic self cleaning as desired by pressing the Auto Self Clean button.

Easy maintenance

As a rule, empty the dust box about **once a year***3

When the dust box becomes full of dust, an indication*4 lets you know it is time to empty it. The box needs to be emptied about once a year, so it is not troublesome.



The Auto Self Clean unit can be washed with water.

*3 Based on the results of dust accumulation tests (assuming collection of approx. 0.2g of dust/month in an approx. 20m² room. In-house investigation.) The amount of dust differs depending on the environment in which the unit is used. Please regularly check the dust box and empty it when necessary.

*4 The indication is a rough guide.

Even when the pre-filter is automatically cleaned, depending on conditions of use and the environment, there may be dirt that cannot be removed from the filter. If you are concerned about greasy dirt or other kinds of stubborn dirt, please regularly remove the filter and clean it.

*1 Testing authority: Boken Quality Evaluation Institute. Test methods: JIS Z 2801 antimicrobial test (film adhesion test). Target: adhesive bacteria. Antibacterial method: antibacterial components in resin. Test results: antibacterial activity value of 2.0 or higher (An antibacterial activity value of 2.0 or higher indicates an antibacterial effect).

Easy Maintenance & Hygienic

Stainless Clean System

Stainless steel anti-bacterial effect keeps it hygienic. The stainless steel used in the pre-filter, flap and net outlet help eliminate bacteria.

- Stainless steel coating flap: Eliminate Bacteria*1
- Stainless net (outlet): Eliminate Bacteria*1
- Stainless steel coated pre-filter*2: Eliminate Bacteria*1
- Silver ion fan: Suppress Bacteria*3
- Washable deodorising filter
- Allergen-free HEPA filter for fine dust
- Auto Self Clean unit

*1 Not all of the bacteria in the air released by the air purifier are eliminated. Antibacterial effect of the (1) stainless pre-filter, (2) stainless flap, and (3) stainless net (outlet) • Testing authority: (1) and (2) Boken Quality Evaluation Institute, (3) Kitasato Research Center for Environmental Science • Test method: JIS Z 2801 (film contact method) • Test item: Attached bacteria • Sterilization method: Using the metal ion contained in stainless steel • Test results: 99% of bacteria eliminated after 24 hours.

*2 Stainless-steel coating.

*3 There is no anti-bacterial effect in the air released by the air purifier. Anti-bacterial effect of the silver ion fan • Testing authority: Boken Quality Evaluation Institute • Test method: JIS Z 2801 (film contact method) • Test item: Attached bacteria • Anti-bacterial method: Anti-bacterial components included into the silver ion fan • Test results: Anti-bacterial activity value 5.1 (anti-bacterial effect is present when the activity value is more than 2.0).

User-friendly

Glass panel


Flat front glass panel is easy to clean – simply wipe off dirt. Reinforced glass is also scratch-resistant. Color does not fade and matches home interiors.



Touch panel operation

Touch panel has been incorporated on front glass panel.

Clean monitor changes its color to notify status
Blinks when PM2.5 sensor is activated



Slim design

Sleek, slim design of this large capacity unit occupies less space and is an ideal match for modern interiors.




Width 360mm • Depth 291mm


Deodorising

Washable deodorising filter Replacement not necessary for approx. 10 years*1

Filter can be washed with water to restore deodorising power*2. This helps to reduce four major types of odour bases: nitrogen, aldehyde, acid and sulphur components.



How deodorising power is restored



*1 In accordance with the JEM1467 standard of the Japan Electrical Manufacturers' Association. The number of years after which the odour elimination rate decreased by half with 5 cigarettes smoked per day. Maintenance or replacement may be required depending on conditions of use and the type and strength of odours.

*2 Depending on the odour, washing with water may not eliminate it. Restoration of deodorising performance by washing with water gradually declines.

Nitrogen-based Ammonia (Pet odours, etc.) Trimethylamine (Foul fish odours, etc.)	Aldehyde-based Acetaldehyde (Cigarette odours, etc.) Isovaleraldehyde (Odours of grilled meat, etc.)	Acid-based Acetic acid (Cooking odours including pickling odours) Isovaleric acid (Body odours, odour of laundry drying indoors, etc.)
--	---	---

Results of odour elimination tests in a 25m³ test space using single odour components. Odour elimination performance differs under conditions of actual use in a room. Tests performed by Hitachi.

Sulphur-based Hydrogen sulfide (Odours from drain outlet and toilets) Methylmercaptan (Odours from rotten vegetables)

Results of deodorising performance tests performed in a 1m³ test space with single odour components. Deodorising performance differs depending on the space where the unit is actually used. Testing authority: Japan Food Research Laboratories

Dust Collection Performance

Allergen-free HEPA for fine dust

Effectively captures fine particles

Multi-layered structure of Allergen-Free HEPA Filter for fine dust effectively catches fine particles including dust, cedar pollen and airborne mould. It also suppresses the PM2.5.

HEPA Filter collects 99.97% or more dust containing fine particles of 0.3µm at a rated air flow

Based on performance of a single HEPA filter complying with the JIS Z 8122. Overall room dust removal performance may differ.


Suppresses activity of captured allergen substances

The allergen-free components of the HEPA Filter for fine dust suppress the activity of cedar, birch & ragweed pollen, dust mite dung & cat dandruff that have been captured.

• Testing authority: Nichinichi Pharmaceutical Co., Ltd • Test method: ELISA • Suppression method: Application of anti-allergen agent to filter • Test results: Cedar pollen 96% suppression, birch pollen 90%, ragweed pollen 96%, American dust mite dung 93%, European dust mite dung 91%, and cat dandruff 85%. Value in percentage calculated by Hitachi

Air Purifier suppresses airborne viruses and bacteria*3

This is the effect on airborne viruses and bacteria after 13 minutes in a 25m³ test space, not the proven effect in a space where the filter is actually used. Effects may differ according to conditions and method of use. Tests performed conform to the Japan Electrical Manufacturers' Association standard (HD-124). *3 Virus/ bacteria suppression effect • Testing authority: Kitasato Research Center for Environmental Science • Test method: Performance evaluation test conforming to the Japan Electrical Manufacturers' Association standard (HD-124) conducted in a 25m³ test space. Same test applied for bacterial suppression effect • Test item: 1 type of airborne virus/1 type of airborne bacterium • Test results: 99% or more suppressed in 13min • Model used: EP-L110E (with max air flow).



Wide and speedy dust collection

Applicable to a 79m² floor space. Rapidly collects dust in just 6 minutes in a 13m² room.


Increased air intake surface area achieved on the back lateral sides. By widely collecting dust from both sides, a 13m² room can be quickly purified in a mere 6 minutes.

Dust collection capacity applicable to a floor space of up to **79m²**

Cleans a **13m²** room in just **6 minutes**

Time taken to clean
Displays time taken for dirt (powdered dust) of standard thickness to reach a level lower than the standard amount of such powdered dust in a room of approx. 13m².

Speedy air purifying with a massive air volume of **11m³** per min.



PM2.5 sensor detects fine particles, cleans them up with max air flow

Purifies PM2.5 particles with a massive air volume – much quicker than the normal automatic air purification mode


Switches to high-sensitive detection mode and purifies fine dust with max air flow operation.*1 HEPA filters enable the collection of fine particles*2 of 0.1µm and larger (0.5µm or larger with the dust sensor detection). Continues super-sensitive patrol operation even after cleaning the air.

*1 Comparison with normal automatic air purification mode. Time required for reducing an initial concentration of approx. 1,000 µg/m³ to 35 µg/m³. Normal automatic air purification mode: 38 min, PM2.5 sensing automatic operation mode: 20 min. Surveyed by Hitachi.


*2 Cigarette smoke.

99% of 0.1 to 2.5µm particles caught*3 – ready to remove PM2.5 particles

New particles entering from outside during ventilation or by other means are not considered here. PM2.5 is a collective term for particulate matter of 2.5µm or less in diameter. Removal of particulate matter less than 0.1µm has not been verified. Further, not all harmful substances in the air can be removed. Results were obtained in a sealed 32m³ space and not in an actual living space.



Operation mode automatically changes according to fine particle concentration



*3 Odour sensor does not activate during the PM2.5 sensing mode

Low operating sound and energy-saving

Special emphasis has been placed on reducing noise during operation and lowering electricity cost

Low noise operation

20 dB	Sound of leaves rustling on a tree	30 dB	Pendulum of a wall clock
40 dB	Inside a library	50 dB	Inside a regular office

	Silent	Medium	High	Max
EP-L110E	14dB	25dB	32dB	55dB

eco operation cuts energy consumption by up to 14%*1 compared to normal automatic operation

When the air is clean or the level of humidity is suitable, the fan automatically pauses and resumes operation every hour.

*1 Energy consumption compared between automatic operation and ECO operation in air purifying mode. Automatic operation: 6.8Wh, ECO operation: 5.6Wh. Tested by Hitachi. Reduction rate of power consumption varies depending on how dirty the air is. Reaction toward dealing with dirty air and corresponding to humidity changes may be slower compared to normal operation mode.

EP-L110E



Hitachi's Air Purifiers were awarded the Allergy UK Seal of Approval in recognition of their proven ability to reduce exposure to allergens.

- Tested by Allergy UK (The British Allergy Foundation)
- Tested with house dust mites and pollen
- Applies to EP-L110E, EP-A9000, EP-M70E, EP-A8000, EP-A7000, EP-A6000, EP-A5000 and EP-A3000

Clean air mode	Purifying time (At max air flow)*2	6 min in a 13m ² room			
	Recommended applicable floor space for air purification (At max air flow)	~ 79m ²			
Clean air and humidifying mode	Purifying time (At max air flow)*2	10 min in a 13m ² room			
	Recommended applicable floor space for air purification (At max air flow)	~ 50m ²			
	Humidifying amount (At max air flow)*3	Approx. 800 mL/h			
	Recommended applicable floor space for humidifying	<table border="1"> <tr> <td>Room with wooden flooring</td> <td>~ 22m²</td> </tr> <tr> <td>Modern prefabricated room</td> <td>~ 37m²</td> </tr> </table>	Room with wooden flooring	~ 22m ²	Modern prefabricated room
Room with wooden flooring	~ 22m ²				
Modern prefabricated room	~ 37m ²				
	Air flow amount (50/60Hz at max mode)	11.0m ³ /min			
	Auto Self Clean	○			
	Wide and speedy dust collection	○			
	PM2.5 sensor	○			
	HEPA filter	○			
	Washable deodorising filter	○			
	Stainless clean system	○			
	Glass panel	○			
	Touch panel operation	○			
	Off timer	4 hours / 2 hours			
	Room temperature indication	○			

*2 Time taken to clean: Displays time taken for dirt (powdered dust) of standard thickness to reach a level lower than the standard amount of such powdered dust in a room of approx. 13m².


*3 In accordance with the JEM1426 standard of Japan Electrical Manufacturers' Association

Auto Self Clean makes maintenance easy. And air drawn in from a wide area enables the collection of dust in a 13m² room in just 6 minutes.

Mirror

Stainless Clean System

The stainless filter is not only hygienic but also easy to clean.



*Applies to the model EP-A9000 and EP-M70E.

*1 Not all of the bacteria in the air released by the air purifier are eliminated. Antibacterial effect of the (1) stainless pre-filter, (2) stainless flap, and (3) stainless net (outlet) • Testing authority: (1) and (2) Boken Quality Evaluation Institute, (3) Kitasato Research Center for Environmental Science • Test method: JIS Z 2801 (film contact method) • Test item: Attached bacteria • Sterilisation method: Using the metal ion contained in stainless steel • Test results: 99% of bacteria eliminated after 24 hours.

*2 There is no anti-bacterial effect in the air released by the air purifier. Anti-bacterial effect of the silver ion fan • Testing authority: Boken Quality Evaluation Institute • Test method: JIS Z 2801(film contact method) • Test item: Attached bacteria • Anti-bacterial method: Anti-bacterial components included into the silver ion fan • Test results: Anti-bacterial activity value 5.1 (anti-bacterial effect is present when the activity value is more than 2.0).

Allergen-free HEPA filter for fine dust

Effectively captures fine particles

HEPA Filter collects **99.97% or more** dust of 0.3µm


Collects 99.7% or more dust containing fine particles of 0.3µm at a rated air flow. Based on performance of a single HEPA filter with the JIS Z 8122. Overall room dust removal performance may differ.



Wide & Speedy Dust Collection

Speedy air purifying with a massive air volume of 9m³* per min. Applicable to a 68m²* floor space.

*Applies to the model EP-A9000.



Other Features

- Powerful humidification at 800mL/h (EP-A9000) & 700mL/h (EP-M70E)
- Washable deodorising filter
- User friendly touch panel operation panel
- Low operating sound and energy-saving

EP-A9000



Applicable Floor Space for Air Purifying ~68m²

EP-M70E



Applicable Floor Space for Air Purifying ~53m²

EP-NZG70J



Applicable Floor Space for Air Purifying ~53m²

